

Technical Sheet ADAPTA



Swivel base:

- 65 cm. Ø Conical base in Polished Aluminium or Nylon
- Rubber Castors (Certified by LGA QualiTest)
- Gas lift with gas pump (UNI 9084/2002)
- Mechanisms:
 - Independent synchronized mechanism with 5 positions rule EN-1355-2.
 - Permanent contact mechanism ANSI-BIFMA X5.1-2002/16.



4 leg chair:

- 2 cm. Ø rounded steel tube with 1,5 mm thickness.
- Finished painted in black.



Cantilever:

- Rectangular steel tube with 1,5 mm thickness.
- Finished in chrome or painted in grey.

Tecnical Sheet ADAPTA

SEAT - BACK - PAIR OF ARMS

Materials:

- Seat interior of beech plywood with foam coated with an injection of polyurethane with a density (hard) of 30 Kg. rule EN-ISO-845.
- Back interior of plastic injected with polypropylene with foam coated with an injection of polyurethane with a density (soft) of 30 Kg. rule EN-ISO-845.
- Seat exterior: plastic injected with polypropylene.

Pair of arms:

- Internal steel frame and chrome exterior.
- Height (7 positions), front/back and depth adjustments.
- Nylon armrest.

Upholstery:

- Water based solvent free glue (polychloroprene polymer resin base)
- Fabric: see upholstery technical sheet.

