

Technical Sheet FAST



Base Giratoria:

- 60 cm. Ø nylon base.
- Rubber Castors (Certified by LGA QualiTest)
- Gas lift with gas pump (UNI 9084/2002)
- Permanent contact mechanism ANSI-BIFMA X5.1-2002/16.



4 leg chair:

- 2 cm. Ø rounded steel tube 1,5 mm thickness.
- Finished painted in black.



Cantilever:

- Rounded steel tube 1,5 mm thickness.
- Finished painted in black.



Stool:

- Gas pump height 240 mm.
- Nylon ring height adjustable footrest.
- Optional: nylon anti-slip gliders.

Technical Sheet FAST

SEAT - BACK - PAIR OF ARMS

Materials:

- Seat interior injected with recyclable polypropylene with foam coated with an injection of polyurethane with a density (hard) of 30 Kg. rule EN-ISO-845.
- Back interior of plastic injected with recycled polypropylene with foam coated with an injection of polyurethane with a density (soft) of 30 Kg. rule EN-ISO-845.
- Seat exterior: plastic injected with recycled polypropylene.

Pair of arms:

- Fixed nylon injection.

Upholstery:

- Water based solvent free glue (polychloroprene polymer resin base)
- Fabric: see upholstery technical sheet.

